

MOTOR CAPACITOR-CBB60


Suntan®

ELECTRICAL APPARATUE USE METALLIZED FILM WITH PRECISELY QUALITY CONTROL

FEATURES

- Low D.F. (dissipation factor), good self-healing character
- High I.R. (insulation resistance)
- High safety & high reliability
- Anti-Striking current, strong over-carrier capacity


TS11




S P E C I F I C A T I O N S

OPERATING CONDITION	-40°C ~ +85°C		Withstand voltage test	GB/T3667.1-2016 IEC/EN60252.1
CAPACITANCE RANGE	1uF~100uF(TS11-10~21)			
CAPACITANCE TOLERANCE	J(±5%)、K(±10%)		Test area	Test voltage
RATED VOLTAGE	250V 450V (AC)		T-T	rated voltage
WITHSTAND VOLTAGE			T-C	2400VAC(If all shell made of insulating materials, without any test in this project)
				time
				2s
				/
DISSIPATION FACTORY	<0.004 100Hz (TS11-10~21)			
INSULATION RESISTANCE	≥3000S			


TS11-10




TS11-11




TS11-12




TS11-13




TS11-14




TS11-15




TS11-16




TS11-17




TS11-18




TS11-19(only for D:30mm)



TS11-20



TS11-21



Please visit our website to get more update data, those data & specification are subject to change without notice.

MOTOR CAPACITOR-CBB60

Suntan®

ELECTRICAL APPARATUE USE METALLIZED FILM WITH PRECISELY QUALITY CONTROL

FEATURES

TS11

- Low D.F. (dissipation factor), good self-healing character
- High I.R. (insulation resistance)
- High safety & high reliability
- Anti-Striking current, strong over-carrier capacity

Dimensions (mm)

CAP	TS11-11				TS11-12				TS11-13				TS11-14			
	250VAC		450VAC		250VAC		450VAC		250VAC		450VAC		250VAC		450VAC	
uF	D	H	D	H	D	H	D	H	D	H	D	H	D	H	D	H
1	30	50	30	50	30	50	30	50	30	57	30	57	30	50	30	50
1.5	30	50	30	50	30	50	30	50	30	57	30	57	30	50	30	50
2	30	50	30	50	30	50	30	50	30	57	30	57	30	50	30	50
2.5	30	50	30	50	30	50	30	50	30	57	30	57	30	50	30	50
3	30	50	30	50	30	50	30	50	30	57	30	57	30	50	30	50
3.5	30	50	30	60	30	50	30	60	30	57	30	57	30	50	30	60
3.75	--	--	--	--	30	50	30	60	30	57	30	57	--	--	--	--
4	30	50	30	60	30	50	30	60	30	57	30	57	30	50	30	60
4.5	30	50	30	60	30	50	30	60	30	57	30	57	30	50	30	60
4.7	30	50	30	60	30	50	30	60	30	57	35	65	--	--	--	--
5	30	50	30	60	30	50	30	60	30	57	35	65	30	50	30	60
6	30	50	35	60	30	50	35	60	30	57	35	65	30	50	35	60
6.3	30	50	35	60	30	50	35	60	30	57	35	65	--	--	--	--
7	30	60	35	60	30	60	35	60	30	57	35	65	30	50	35	60
8	30	60	35	70	30	60	35	70	30	57	35	65	30	60	35	60
9	--	--	--	--	30	60	35	70	30	57	40	70	--	--	--	--
10	30	60	40	70	30	60	35	70	30	57	40	70	30	60	35	70
11	--	--	--	--	30	60	40	70	--	--	--	--	--	--	--	--
12	30	60	40	70	30	60	40	70	35	65	40	70	30	60	40	70
12.5	30	60	40	70	30	60	40	70	35	65	40	70	30	60	40	70
13	35	60	40	70	35	60	40	70	--	--	--	--	35	60	40	70
14	35	60	40	70	35	60	40	70	35	65	40	70	35	60	40	70
15	35	60	40	70	35	60	40	70	35	65	40	70	35	60	40	70
16	35	60	45	70	35	60	45	70	35	65	40	70	35	60	45	70
18	35	70	45	70	35	70	45	70	35	65	40	95	35	70	45	70
20	35	70	45	70	35	70	45	70	35	65	40	95	35	70	45	70
22	35	70	40	90	35	70	40	90	40	70	40	95	35	70	40	90
24	35	70	40	90	35	70	40	90	40	70	40	95	35	70	40	90
25	35	70	45	90	35	70	45	93	40	70	45	95	35	70	45	90
30	40	70	45	90	40	70	45	93	40	70	45	95	40	70	45	90
31.5	--	--	--	--	--	--	--	--	40	95	45	95	--	--	--	--
35	45	70	45	90	45	70	45	93	40	95	45	95	45	70	45	90
40	40	90	50	90	40	90	50	90	40	95	50	106	40	90	50	90
45	45	90	50	90	45	90	50	90	45	95	50	106	45	90	50	90
50	45	90	50	100	45	90	50	100	45	95	50	106	45	90	50	100
55	50	90	50	120	50	90	50	120	45	95	55	120	50	90	50	120
60	50	90	50	120	50	90	50	120	45	95	55	120	50	90	50	120
65	50	90	55	120	50	90	55	120	45	95	55	120	50	90	55	120
70	50	100	55	120	50	100	55	120	50	106	55	120	50	100	55	120
75	50	100	60	120	50	100	60	120	50	106	60	120	50	100	60	120
80	50	100	60	120	50	100	60	120	50	106	60	120	50	100	60	120
85	50	120	60	120	50	120	60	120	50	116	60	120	50	120	60	120
90	50	120	60	120	50	120	60	120	50	116	60	120	50	120	60	120
100	50	120	65	130	50	120	65	130	50	116	65	130	50	120	65	130

Please visit our website to get more update data, those data & specification are subject to change without notice.

MOTOR CAPACITOR-CBB60

Suntan®

ELECTRICAL APPARATUE USE METALLIZED FILM WITH PRECISELY QUALITY CONTROL

FEATURES

TS11

- Low D.F. (dissipation factor), good self-healing character
- High I.R. (insulation resistance)
- High safety & high reliability
- Anti-Striking current, strong over-carrier capacity

Dimensions (mm)

CAP	TS11-15				TS11-16				TS11-17				TS11-18			
	250VAC		450VAC		250VAC		450VAC		250VAC		450VAC		250VAC		450VAC	
uF	D	H	D	H	D	H	D	H	D	H	D	H	D	H	D	H
1	30	57	30	57	30	57	30	57	30	57	30	57	30	50	30	50
1.5	30	57	30	57	30	57	30	57	30	57	30	57	30	50	30	50
2	30	57	30	57	30	57	30	57	30	57	30	57	30	50	30	50
2.5	30	57	30	57	30	57	30	57	30	57	30	57	30	50	30	50
3	30	57	30	57	30	57	30	57	30	57	30	57	30	50	30	50
3.5	30	57	30	57	30	57	30	57	30	57	30	57	30	50	30	60
3.75	30	57	30	57	--	--	--	--	30	57	30	57	30	50	30	60
4	30	57	30	57	30	57	30	50	30	57	30	57	30	50	30	60
4.5	30	57	30	57	30	57	30	50	30	57	30	57	30	50	30	60
4.7	--	--	--	--	--	--	--	--	--	--	--	--	30	50	30	60
5	30	57	35	65	30	57	30	50	30	57	30	57	30	50	30	60
6	30	57	35	65	30	57	30	57	30	57	35	65	30	50	35	60
6.3	30	57	35	65	30	57	30	57	30	57	35	65	30	50	35	60
6.5	--	--	--	--	--	--	--	--	--	--	--	--	30	60	35	60
7	30	57	35	65	30	57	30	57	30	57	35	65	30	60	35	60
7.5	--	--	--	--	30	57	35	65	--	--	--	--	--	--	--	--
8	30	57	40	70	30	57	40	70	30	57	35	65	30	60	35	70
9	30	57	40	70	30	57	40	70	--	--	--	--	30	60	35	70
10	30	57	40	70	30	57	40	70	30	57	40	70	30	60	35	70
11	35	65	40	70	--	--	--	--	--	--	--	--	--	--	--	--
12	35	65	40	70	35	65	40	70	35	65	40	70	30	60	40	70
12.5	35	65	40	70	35	65	40	70	35	65	40	70	30	60	40	70
13	--	--	--	--	35	65	40	70	--	--	--	--	--	--	--	--
14	35	65	40	70	35	65	40	70	35	65	40	70	30	60	40	70
15	35	65	40	70	35	65	40	70	35	65	40	70	30	60	40	70
16	35	65	40	70	35	65	40	70	35	65	40	70	35	60	45	70
18	35	65	40	95	35	65	40	95	35	65	40	95	35	70	45	70
20	35	65	40	95	35	65	40	95	35	65	40	95	35	70	45	70
22	40	70	40	95	40	70	40	95	40	70	40	95	35	70	40	90
24	40	70	40	95	40	70	40	95	40	70	40	95	35	70	40	90
25	40	70	40	95	40	70	45	95	40	70	45	95	35	70	45	90
30	40	70	45	95	40	70	45	95	40	70	45	95	40	70	45	90
33	--	--	--	--	--	--	--	--	--	--	--	--	45	70	45	90
35	40	95	50	106	40	95	45	95	40	95	45	95	45	70	45	90
40	40	95	50	106	40	95	50	106	40	95	50	108	40	90	50	90
45	40	95	50	106	45	95	50	106	45	95	50	116	45	90	50	90
50	45	95	50	106	40	95	50	106	45	95	55	120	45	90	50	100
55	45	95	50	116	45	95	50	116	45	95	55	120	50	90	50	120
60	45	95	50	116	45	95	50	116	45	95	55	122	50	90	50	120
65	45	95	55	120	45	95	55	120	45	95	55	122	50	90	55	120
70	50	106	55	120	50	106	55	120	50	106	55	122	50	100	55	120
75	50	106	60	120	50	106	60	120	50	106	60	120	50	100	60	120
80	50	106	60	120	50	106	60	120	50	106	60	120	50	100	60	120
85	50	116	60	120	50	116	60	120	50	116	60	120	50	120	60	120
90	50	116	60	120	50	116	60	120	50	116	60	120	50	120	60	120
100	50	116	65	130	50	116	65	130	50	116	65	130	50	120	65	130

Please visit our website to get more update data, those data & specification are subject to change without notice.