

SR520 THRU SR5100

SCHOTTKY BARRIER RECTIFIER

REVERSE VOLTAGE 20 to 100 Volts FORWARD CURRENT 5.0 Ampere


FEATURES

- ◆ Low forward voltage drop
- ◆ Low leakage current
- ◆ High forward surge capability
- ◆ High reliability

Mechanical Data

- ◆ Case: DO-27, Mold plastic
- ◆ Epoxy: UL94V-0 rate flame retardant
- ◆ Polarity: Indicated by cathode band
- ◆ Lead: MIL-STD-202E, Method 208 guaranteed
- ◆ Mounting position: Any

DO-201AD(DO-27)



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%

	SYMBOL	SR520	SR530	SR540	SR550	SR560	SR580	SR5100	UNIT
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	20	30	40	50	60	80	100	Volts
Maximum RMS Voltage	V_{RMS}	14	21	28	35	42	56	70	Volts
Maximum DC Blocking Voltage	V_{DC}	20	30	40	50	60	80	100	Volts
Maximum Average Forward Rectified Current	$I_{(AV)}$	5.0							Amps
Peak Forward Surge Current 8.3ms single half sine wave superimposed on rated load (JEDEC method)	I_{FSM}	150							Amps
Maximum Instantaneous Forward Voltage at 5.0A	V_F	0.55			0.70		0.85		Volts
Maximum DC Reverse Current $T_A=25^\circ\text{C}$ at rated DC Blocking voltage $T_A=100^\circ\text{C}$	I_R				0.5				mA
					50				
Typical Junction Capacitance (NOTE 1)	C_J	500			400				pF
Typical Thermal Resistance (NOTE 2)	$R_{\theta JA}$	10							°C/W
Operating Temperature Range	T_J	-55 to +125							°C
Storage Temperature Range	T_{STG}	-55 to +150							°C

Note: 2. Measured at 1.0MHz and applied reverse voltage of 4.0 Volts.

3. Thermal Resistance From Junction to Ambient at .375"(9.5mm) lead length, P.C. board mounted.

SR520 THRU SR5100

SCHOTTKY BARRIER RECTIFIER

REVERSE VOLTAGE 20 to 100 Volts FORWARD CURRENT 5.0 Ampere

RATING AND CHARACTERISTIC CURVES SR520 THRU SR5100

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS





FIG.5-TYPICAL JUNCTION CAPACITANCE



Note: Specifications are subject to change without notice. For more detail and update, please visit our website.